

# Imerback™

## PRODUCT DESCRIPTION

Imerback is a coarse dry ground marble with particle size controlled between 40 and 200 mesh screens.

## PRODUCT

Mineral | Limestone

## APPLICATIONS

- Elastomers & rubber
- Plastics
- Adhesives & sealants
- Caulks & mastics
- Ceiling tiles
- Flooring
- Paint & coatings
- Thermosets
- and more

## TYPICAL PHYSICAL PROPERTIES

|                      |                           |      |
|----------------------|---------------------------|------|
| Physical Form        |                           | Sand |
| Screen Residue       | (+40 Mesh Screen, wt. %)  | 1    |
| Screen Residue       | (-200 Mesh Screen, wt. %) | 15   |
| pH                   | —                         | 8-9  |
| Moisture             | (wt. %)                   | 0.15 |
| Specific Gravity     | (g/cm <sup>3</sup> )      | 2.7  |
| Bulk Density, Loose  | (lbs/ft <sup>3</sup> )    | 90   |
| Bulk Density, Packed | (lbs/ft <sup>3</sup> )    | 115  |

## TYPICAL CHEMICAL ANALYSIS (%)

|                   |    |
|-------------------|----|
| CaCO <sub>3</sub> | 95 |
| Acid Insolubles   | 2  |

## Imerys

### Sales Office:

100 Mansell Court East,  
Suite 300  
Roswell, GA 30076  
United States

### Production Site:

Sylacauga, AL, USA

### Customer Service:

Tel: +1 (888) 277 9636  
Fax: +1 (770) 645 3631

[www.imerys.com](http://www.imerys.com)

July 2019

The data quoted here is believed to be correct and represent the typical value of this product. It is not intended to represent product specifications. Every precaution is taken to ensure the products conform to our published data, but since the products are based on naturally occurring raw materials, we reserve the right to change this data should it become necessary. All recommendations and sales are made on the condition that we will not be held liable for any damages resulting from their use. This provision may not be changed by any of our representatives. Any Health and Safety questions, please refer to our SDS.